

PowerStation Twin V Pro

*High End Fast Charger for
Lithium Ion Digital SLR Batteries*

- Fast charger for 1 or 2 lithium ion batteries
- 2 LCD Displays – 1 for each battery
- 2 charge control systems – 1 for each battery
- Variable charge current – depending on battery capacity
- Battery overheating protection
- Interchangeable battery contact plate
- Modern style housing with slide-out charger cover, turning into a stand-up charger support



Sleek, modern housing with brushed aluminium detail and slide-out cover/stand



Hi-tech fast charger with LCD display



Light-weight 100–240V Universal power adapter & 12V DC Car lead

For Digital SLRs



For Canon Digital SLRs



For Nikon Digital SLRs



For Sony, Panasonic & Leica Digital SLRs



For Olympus, Samsung & Pentax Digital SLRs



DSLR

Futuristic Design

- Interchangeable battery contact plates allow the charging of different Li-Ion batteries from different digital SLR cameras.
- Charging time from approximately 1 to just over 2 hours depending on battery.
- LCD display indicates charging process as well as other functions including 'battery full', 'battery defect' and over heating switch off.
- Twin V Pro converts to battery tester when power is not connected. Battery tester indicates approximate charge level.
- A slide out rotating charger cover, converting to a stand up charger support, gives the Twin V Pro modern styled housing which is extremely slim-line and compact. This allows maximum space in camera bags.

Ideal Travel Companion

- 12V DC input with car lead included – giving the user the flexibility to travel anywhere with the Twin V Pro.
- Multi-voltage switch mode power supply 100-240V, for world wide use.
- Fast charging eliminates long waiting period for charging process to complete, allowing users to capture all their memorable moments.

Twin Battery Compartments

- 1 or 2 Li-Ion batteries can be charged at any one time with the Twin V Pro, allowing additional power options for the ambitious user of digital SLR cameras.
- Each battery has its own independent micro-chip regulated charge control with a sophisticated LCD info display.
- Separate LCD display one for each battery.




LCD Display



Battery Assessment



Charging




5-Stage charge indicator (20%-100%)



Fully Charged



Battery Defect



Battery tester – indicates approximate charge level



Specifications	PowerStation Twin V Pro	
LED indication	charge battery tester	charge progress symbols, state of charge %, "E" error, battery defect, over temperature battery capacity %
Charging time*		from approx. 1 to just over 2 hours
Charge technology		constant current/constant voltage (CC/CV)
Charge current		700 – 1500mA depending on type and number of batteries being charged
Power source	Mains	100V-240V AC 50/60Hz Output 12V 1.25A
	12V DC	12V 400mA DC 2A with Car Lead included
Battery technology		rechargeable Lithium Ion or Lithium Ion Polymer
Dimensions		97H x 130W x 38D (mm)
Weight		96g (excluding battery, mains plug & 12V car lead)

Model Type	Part No	Camera	Plate	Battery
For Canon	1000 540.0	EOS 1000D/500D/450D	T1	LP-E5
		EOS 400D/350D	T1	NB-2LH
		EOS 30D/20D, 5D	T8	NB-511
For Nikon	1000 541.0	D200/D80	T2	EL3e
		D40	T7	EL9
		D50, D70, D70s, D100	T2	EL3
For Sony, For Panasonic, For Leica	1000 543.0	Alpha DSLR-A100/100K/A700	T4	NP-FM55H/FM-500H
		DMC-L1	T3	CGR-S603
		Digilux 3	T3	BP-DC3
For Olympus, For Samsung, For Pentax	1000 542.0	E-400, E300, E-410, E-550	T6	BS-BLS1
		E-330, E-500, E-1	T2	BS-BLM1
		GX10	T2	SLB-1674
		K10D	T2	D-L150

Also Available For PRO and Semi PRO Camcorders

see Twin V Pro Video brochure for details



For Sony, Panasonic,
Canon & JVC Camcorders
part no. 1000 550.0